

TECHNICAL PRODUCT DATA SHEET

140 RECYCLED RUBBER WALKBOARD PADS**PRODUCT DESCRIPTION**

Product Use: Malarkey Roofing Products™ (Malarkey) 140 RECYCLED WALKBOARD is used as walk pad for traffic areas on the roof to protect the roof from traffic; i.e. around the hatch, around rooftop units, and walk ways to the units.

Composition and Materials: 140 RECYCLED WALKBOARD is made from recycled rubber (100% of the rubber is recycled, tires and binders).

Application Standards: Approval for use on all Malarkey roof systems.

TECHNICAL DATA

Typical average properties, 3' x 4' pad:

Weight	3 lbs. per square foot, 36 lbs. per pad
Dimensions	3' x 4'
Thickness	1/2"
Color	Black

Electrostatic Propensity AATCC Test Method
Compression & Recovery

NEG 0.9 KV Maximum Voltage
Immediate 98.1%
After 24 Hours 99.2%
After 96 Hours 99.7%

APPLICATION PROCEDURES

Malarkey 140 Recycled Walkboard may be installed by spot adhering in with a One-Part Polyurethane adhesive; i.e. ChemRex CX-948, Sikaflex-1A or Chem Link M-1. (Adhere 4 corners and one spot in center. Spots of adhesive should be at least silver dollar size). **Do not use asphalt cut-back adhesives.** Contact Malarkey for further details.

TECHNICAL SERVICES

Malarkey has technical services assistance available for all phases of built-up roof coverings and requirements. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191; Weekdays 7:00 a.m. to 5:00 p.m. Pacific Time.

AVAILABILITY

Malarkey 140 walkboard is available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.

Effective 12.07 | Supersedes all previously published data.

For most current version, go to www.MalarkeyRoofing.com