



SAFETY DATA SHEET

1 PRODUCT AND COMPANY IDENTIFICATION

Product Type: Malarkey Flexor™ SBS Polymer Modified Self-Adhering Polyester FR Cap Sheet

Trade Names:

435 OmniSeal™ Cap Plus
435R OmniSeal™ Cap Plus

Use: Low slope, self-adhering cap sheets

Manufacturer:

Malarkey Roofing Products
P.O. Box 17217
3131 N. Columbia Blvd.
Portland, OR 97217
Phone: 503-283-1191
www.malarkeyroofing.com

Emergency Contact:

CHEMTREC®: 1-800-424-9300 (24 HOUR)

2 HAZARD(S) IDENTIFICATION

Signal Word: WARNING

Carcinogenicity: Category 2A

Skin Irritation: Category 2

HAZARD STATEMENTS

- Causes skin and eye irritation.
- May cause an allergic skin reaction.
- Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

- Read instructions before use.
- Use in a well-ventilated area.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust.
- Wear proper Personal Protective Equipment including gloves/protective clothing/eye protection/face protection and respirator where appropriate.
- Do not eat, drink or smoke when using this product.
- Thoroughly wash hands and exposed skin after handling.

GHS CLASSIFICATION



3 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS #	Ingredient %
Asphalt	8052-42-4	40 - 45
Colemanite	12291-65-5	13 - 23
SBS	9003-55-6	2 - 8
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	64742-52-5	1 - 4
Mineral Granules	Mixture	30 - 40

4 FIRST-AID MEASURES

Eye contact: Immediately flush eyes with plenty of cool water for at least 20 minutes, occasionally lifting the eye lids to ensure thorough rinsing. Get medical attention if irritation persists.

Skin contact: Clean any exposed skin with warm soapy water if possible. If not, and a waterless hand cleaner is used, it should be without pumice. Do not use solvents or thinners to remove material from skin. Get medical attention if irritation persists or develops.

Ingestion: If swallowed, do not induce vomiting. If vomiting occurs, keep head lower than hips to avoid aspiration of vomit into the lungs which can cause inflammation or pneumonitis. Call poison control center or get immediate medical attention.

Inhalation: If inhalation of dust occurs, remove person to fresh air. Drink water to clear throat or blow nose to clear. If not breathing, give artificial respiration or give oxygen by trained personnel and get immediate medical attention.

Notes to physician: Treatment should be based on removing the source of irritation with treatment of symptoms as necessary.

5 FIRE-FIGHTING MEASURES

Flash point: 525°F minimum (274°C), Cleveland Open Cup

Auto-ignition temperature: > 650°F

Extinguishing media: Dry chemical, CO₂, or foam fire extinguisher should be used for controlling small fires. Avoid use of straight-stream water.

Special firefighting procedures: Avoid breathing fumes. Firefighters should wear NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.

Unusual fire or explosion hazards: When heated, fumes may burn if ignition source is provided. Petroleum asphalt fumes can explode if emitted in an enclosed environment and supplied with an ignition source. Burning product will cause thick black smoke.

Hazardous combustion products: Carbon monoxide, carbon dioxide, ozone, hydrogen sulfide, oxides of sulfur and various hydrocarbons during heating or burning. These combustion products are not expected unless product is heated or burned.

6 ACCIDENTAL RELEASE MEASURES

Precautions if material is spilled or released: Pick up large pieces. Leather or cotton gloves must be worn when handling. Do not dry sweep dusts or blow with compressed air. Wet sweep only.

Waste disposal methods: It is highly recommended this product be recycled. Otherwise, dispose in accordance with applicable Federal, State, and Local regulations. Do not burn.

7 HANDLING AND STORAGE

Storage temperature: Store away from heat and all ignition sources and open flames in accordance with applicable laws and regulations. Product should not be burned or heated using a direct flame.

Precautions to be taken in handling and storage: Follow recommended work practices and use recommended personal protective clothing and equipment.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Components	CAS #	OSHA		ACGIH	
		TWA	STEL	TWA	STEL
Asphalt	8052-42-4	NE	NE	0.5 mg/m ³ ^a	NE
Colemanite	12291-65-5	NE	NE	NE	NE
Styrene Butadiene Copolymer	9003-55-6	NE	NE	NE	NE
Quartz (a component of Dacite Porphyry)	14808-60-7	0.3 / 0.1 ^b	NE	0.025 mg/m ³ respirable fraction	NE

NE = Not Established

^a = Asphalt Fume as benzene-soluble inhalable aerosol

^b = Total Nuisance Dust / Respirable Dust (mg/m³)

Respiratory protection: Normally not needed in well-ventilated areas unless cutting with power tools. If applicable exposure standards are exceeded or can be exceeded introduce ventilation to remove dust. If increased ventilation is not possible, use a NIOSH approved air-purifying respirator. If concentrations are sufficiently high that this respirator is inadequate, or high enough to cause oxygen deficiency, use a positive pressure self-contained breathing apparatus (SCBA). Follow all applicable respirator/SCBA use, fitting, and training standards and regulations.

Ventilation: Use only with adequate ventilation to maintain exposures below applicable exposure limits.

Eye protection: Safety glasses with side shields must be used when handling.

Skin protection: Must wear leather or cotton gloves during application and tear-off activities.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance and odor: Solid material with granular surfacing, adhesive backing w/release film, very low odor.

Odor threshold: Not Applicable

Vapor pressure: Not Applicable

pH: Not Applicable

Specific gravity/relative density: >2

Vapor density (Air = 1): Not Applicable

Viscosity: Not Applicable; solid

Boiling point: > 700°F

Melting point: > 200°F

Solubility (IES): No data available

Flash point: > 525°F

Evaporation rate (Butyl Acetate = 1) : < 0.1

Flammability (Solid and Gas): Not Applicable

Initial boiling point and boiling range: Not Applicable

Auto-ignition temperature: >343°C/680°F

Upper/lower flammability or explosive limits: Not Applicable

Decomposition temperature: Not Applicable

10 STABILITY AND REACTIVITY

Stability: Stable

Reactivity: Reactivity will not occur.

Conditions to avoid: Keep from heat, sparks, open flame and other sources of ignition. Avoid contact with strong oxidizing agents. PRODUCT SHOULD NOT BE BURNED OR HEATED USING A DIRECT FLAME DEVICE.

Hazardous reaction: Polymerization will not occur.

Incompatibility (materials to avoid): Strong acids or bases, oxidizing agents and selected amines.

Hazardous combustion products: Carbon monoxide, carbon dioxide, ozone, hydrogen sulfide, oxides of sulfur and various hydrocarbons during heating or burning. These combustion products are not expected unless product is heated or burned.

11 TOXICOLOGICAL INFORMATION

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Inhalation: Dust may cause upper respiratory irritation.

Ingestion: May cause harmful effects if swallowed.

12 ECOLOGICAL INFORMATION

Ecotoxicity: No data available.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Other adverse effects (GHG, Ozone): No data available.

13 DISPOSAL CONSIDERATIONS

This product has not been regulated as a hazardous waste by the USEPA. Recycling is recommended. Otherwise, dispose in accordance with Federal, State, and Local regulations. Do not burn. Do not dispose as sewage.

14 TRANSPORT INFORMATION

This product is not regulated as a hazardous material for transport under 49 CFR or for vessel transport under the IMDG Code.

UN number: Not applicable

UN proper shipping name: Not applicable

Packing group, if applicable: Not applicable

Environmental hazards: Not applicable

Transport in bulk: Not applicable

Special precautions: Not applicable


15 REGULATORY INFORMATION

Toxic Substances Control Act (TSCA): Some components in this product are listed on the TSCA Inventory.

Comprehensive Environmental Response Compensation and Liability (CERCLA): None

Superfund Amendments and Reauthorization Act of 1986 (SARA), Title III, Section 302 Extremely Hazardous Substances: None

Section 311/312 Hazard Categories: Immediate Health; Delayed Health; Fire Hazard

California Proposition 65:  **WARNING:** This product can expose you to chemicals, including bitumen, which is known to the State of California to cause cancer. For more information go to:

www.P65Warnings.ca.gov.

16 OTHER INFORMATION

HMIS RATING

HEALTH: 1
FLAMMABILITY: 1
REACTIVITY: 0
PERSONAL PROTECTION: B



DISCLAIMER

Malarkey Roofing Products® is furnishing this information without warranty, expressed or implied, and it is accurate to the best of our knowledge. The data on this sheet are related only to the specific material designated herein. Malarkey Roofing Products® assumes no legal responsibility for use or reliance upon these data.