

707 LOW VOC ASPHALT PRIMER

Note: Malarkey Roofing Products™ (Malarkey) inventory SKU numbers for this product: 707

Product Description

Product Use: Malarkey Roofing Products 707 Asphalt Primer is designed as a prime coat for concrete, metal, composition roofing or any non-asphaltic surfaces. 707 Asphalt Primer assists in adhesion of all asphalt products to masonry, metals or other asphaltic surfaces. It is a light-bodied liquid suitable for brushing, rolling or spraying.

Composition and Materials: 707 Asphalt Primer is manufactured with selected, specially blown asphalt and petroleum solvents.

Technical Data

Typical Properties:

Weight/gallon	7.4-7.9 lbs. (3.4-3.6 Kg)
Residue by evaporation, %	60 min.
Tack Time (50% RH, 70°F)	30 minutes
Full Cure	24-48 hours
Application Temperatures	35° - 120°F (1.7° -49°C)
Container Sizes	5 gallons 55 gallons

As manufactured, 707 Asphalt Primer meets the requirements of ASTM D41.

Application

Application Procedure: 707 Low VOC Asphalt Primer is ready to use. Do not thin. Standard coverage is approximately 100 ft²/gal on concrete, roofing and roofing felt; 200 ft²/gal over metal. Apply with a brush, roller or spray equipment. Spray equipment should be set at 100-500 PSI, 0.019-0.031 Tip Size, @0.5-2.0 GPM.

Precautions: Do not store 707 Low VOC Asphalt Primer at temperatures above 110°F (43°C). Do not transport in the passenger compartment of any vehicle; transport or store in cargo compartment.

Technical Assistance: Malarkey has technical services assistance available. Contact Malarkey for details at (800) 545-1191 or (503) 283-1191, weekdays 7:00 a.a. to 5:00 p.m. Pacific Time.

707 (Low VOC) Asphalt Primer and other Malarkey products are available throughout North America and Pacific Rim countries. Visit www.MalarkeyRoofing.com for additional product information and availability.