

TECHNICAL DETAILS

WEIGHT/SQUARE 200 lbs. 90.7 kg	EXPOSURE 5 ⁵ / ₈ " 143 mm
SHINGLES/SQUARE 66 3 bundles/square	GRANULE ADHESION 0.45 g Typical Results
WIDTH ± 1/8" 13 ¹ / ₄ " 337 mm	LENGTH ± 1/8" 39 ³ / ₈ " 1.0 m
SQUARES/PALLET 16	

TEST COMPLIANCE

ASTM D7158 Class H	ASTM D3462
ASTM D3161 Class F	ASTM D3018 Type I
ASTM E108 Class A Fire Rating	ICC APPROVAL ESR-3150
	

FEATURES & BENEFITS

- Algae resistant
- Superior granular embedment
- 25-year Limited Shingle Warranty
- Limited Wind Warranty

ALGAE-RESISTANT TRADITIONAL 3-TAB FIBERGLASS SHINGLES



PRODUCT USE

Dura-Seal™ AR is a 3-tab, metric-based, asphalt shingle. The metric dimension translates to fewer shingles required per square measurement than standard-sized shingles. Please consult Malarkey's Technical Services Department for approval of roof systems.

COMPOSITION & MATERIALS

Dura-Seal™ AR is manufactured on a woven fiberglass mat and impregnated on both sides with bitumen (asphalt) that is compounded with a fire-retardant mineral stabilizer. Dura-Seal™ AR is surfaced with algae-resistant ceramic granules for ultraviolet protection and weatherability.

APPLICATION

Shingles should be applied over a Malarkey underlayment or an approved, code-compliant substitute. Installation instructions are available on the shingle wrapper, at WWW.MALARKEYROOFING.COM, or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails for this purpose. Staples are not allowed.

PRECAUTION

For best results, Malarkey recommends Dura-Seal™ AR shingles be protected from the weather and stored in a cool, dry, well-ventilated area until applied. Do not double-stack pallets. Do not use on roofs where the slope is less than 2:12 (2" [51 mm] per 12" [305 mm]). For slopes 2:12 up to 4:12 (4" [102 mm] per 12" [305 mm]), additional deck protection is required. The Dura-Seal™ AR shingle has a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. On slopes greater than 21" (533 mm) per 12" (305 mm), hand-sealing of tabs and six nails are required. Contact Malarkey for further conditions and instructions.

WARRANTY

Dura-Seal™ AR carries a 25-year Limited Product Warranty, a 60 mph (97 kph) Limited Wind Warranty, and a 5-year Algae Resistant System Warranty. Contact your roofer, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Dura-Seal™ AR and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products® (Malarkey) inventory SKU number for this product: 203 Dura-Seal™ AR

TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available. Contact Malarkey for details: Call weekdays 7:00 am to 5:00 pm PST, at 800.545.1191 or 503.283.1191. technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217

Effective 12/16
Supersedes all previously published data

Check for most current version on our website.