

TECHNICAL DETAILS**COVERAGE RATE***54 ft² - 63 ft² per 1 kg
5 m² - 5.9 m² per 2.3 lbs.**PACKAGING**1-kg cans
2.3 lbs. each**FORM/COLOR**Fluid
Gray**CURE TIMES^Δ****1 HOUR @**86° F
30° C**2 HOURS @**68° F
20° C**3 HOURS @**50° F
10° C**4 HOURS @**37° F
3° C**FEATURES & BENEFITS**

- Promotes bonding to metal substrates
- EZ Seal membranes are monolithic, flexible and seamless
- Ideal for access-restricted areas and difficult waterproofing conditions

* Gross yield/container is approximate. See recommendations for specific applications. Yields will vary depending upon system selected and the smoothness and absorbency of substrate.

^Δ Cure times are approximate, provided as a guideline, and may vary.

EZ SEAL METAL PRIMER

PRODUCT USE

EZ Seal Metal Primer promotes bonding of EZ Seal liquid-applied roofing membranes to various metal substrates. Malarkey Roofing Products® EZ Seal System is waterproof, flexible, self-adhering, and ideal for access-restricted and difficult waterproofing conditions. EZ Seal conforms and bonds directly to the substrate, eliminates the need for caulk and pitch pans, and is virtually maintenance-free.

COMPOSITION & MATERIALS

EZ Seal Metal Primer is a high performance, solvent-borne, polymer-based, single-component primer.

APPLICATION/INSTALLATION

EZ Seal Metal Primer is a coupling agent and used in high traffic areas, on detail work with small contact areas, metal drain bowls, and terminations of edge metal. Prepare metal substrates as specified in the EZ Seal Application Instructions, and stir before use. Application over the primer should take place within 24 hours. Contact Malarkey's Technical Services Department for details.

PRECAUTIONS

EZ Seal Metal Primer is harmful by inhalation and irritating to eyes and skin. Vapors may form an explosive mixture with air so keep away from heat, flame and ignition sources. To ensure safety when handling, the user should wear appropriate PPE, including respirator in enclosed spaces. Wash thoroughly after handling. Consult SDS for complete details.

EZ Seal Metal Primer shall be stored in its original container with adequate ventilation. When not in use, keep container closed in a cool, dry location. In case of spill, absorb with liquid-binding material, collect, and dispose of waste in accordance with federal, state and local regulations. Material and container must be disposed of as hazardous waste.

EMERGENCY INFORMATION:

For Chemical Emergency, Spill Leak, Fire Exposure or Accident
Call CHEMTREC Day or Night; in North America 800-424-9300

Substrates must be clean, dry, free of surface moisture, oil, grease, contaminants, and any other material or condition which would adversely effect bonding of EZ Seal to the substrate.

WARRANTY

Malarkey Roofing Products® offers various warranties to meet specific requirements. Contact your roofer, local distribution center or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

EZ Seal and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products® (Malarkey) inventory SKU number for this product: 752-1 EZ Seal Metal Primer

TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available.
Contact Malarkey for details:
Call weekdays 7:00 am to 5:00 pm PST,
at 800.545.1191 or 503.283.1191.
technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217