

**TECHNICAL DETAILS**

<b>VOC CONTENT</b> 50 grams/liter max.	<b>SOLAR REFLECTANCE</b> ≥ 0.81
<b>APPLICATION RANGE</b> 45°F-135°F (7°C - 57°C)	<b>APPLICATION RATE</b> 1.0 gal. per 100 ft. <sup>2</sup> (0.6 L/m <sup>2</sup> )
<b>PACKAGING</b> 3.5 gal. pails 13.3 L	<b>COLOR</b> White

**TEST COMPLIANCE**

<b>ASTM</b> C1549
----------------------

**FEATURES & BENEFITS**

- High solar reflectance
- Excellent hiding ability
- Lead, asbestos and mercury free

**TOUCH-UP ROOF COATING****PRODUCT USE**

Malarkey RCap™ Touch-Up Roof Coating is a low VOC liquid that cures into a flexible elastomeric membrane with high solar reflectance and excellent hiding ability (bleed-through resistance) even when applied over new asphalt surfaces. RCap™ Touch-Up is typically used to 'touch-up' areas on 524 RCap™ Plus, 624 RCap™, and 626 Paragon® RCap™ SBS, reflective-coated cap sheet installations such as field and flashing side and end laps, penetrations, and other areas where asphalt or cold adhesive bleed-out is present. Product is lead, asbestos, and mercury free.

**APPLICATION**

Apply RCap™ Touch-Up by roller or brush. Coverage rate is typically one (1) gallon per 100 ft<sup>2</sup> (0.6 L/m<sup>2</sup>), but may vary depending upon surface contours. When applied in a four (4) inch (102 mm) wide swath of a 16 mil wet film thickness, product will yield an approximate coverage of 300 lineal feet (91.4 m) per gallon. Apply RCap™ Touch-Up directly to cooled asphalt bleed-out at side laps, end laps, or onto granules that have been broadcast into hot asphalt bleed-out. Cold adhesive bleed-out should cure for approximately 30 days (depending upon geographical location and ambient temperatures) before applying RCap™ Touch-Up. Allow at least four (4) hours between coats.

**PRECAUTIONS**

All surfaces must be dry (not damp) and free of dust, dirt, oil, loose granules and all other foreign matter. For best results, apply on a clear, warm, sunny day with temperatures at or above 45°F (7°C) but with surface temperatures below 135°F (57°C). Do not apply if there is a threat of rain within 24 hours of application. Keep container closed when not in use. Store and use only in well-ventilated areas. Avoid prolonged breathing of vapor. Use proper protection and adequate ventilation when using this product.

**WARRANTY**

Malarkey Roofing Products® offers various warranties to meet specific requirements. Contact your roofer, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

RCap™ Touch-Up Roof Coating and other Malarkey products are available throughout North America and Pacific Rim countries. Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.

Note: Malarkey Roofing Products® inventory SKU number for this product: 824 RCap™ Touch-Up Roof Coating

**TECHNICAL ASSISTANCE:**

Malarkey has technical services assistance available.  
Contact Malarkey for details:  
Call weekdays 7:00 am to 5:00 pm PST,  
at 800.545.1191 or 503.283.1191.  
[technicalinquiries@malarkeyroofing.com](mailto:technicalinquiries@malarkeyroofing.com)

**CORPORATE OFFICE:**

3131 N. Columbia Blvd. Telephone: 503.283.1191  
Portland, OR 97217-7472 or 800.545.1191  
P.O. Box 17217 Fax: 503.289.7644  
Portland, OR 97217-0217

Effective 7/16  
Supersedes all previously published data

Check for most current version  
on our website.