

**TECHNICAL DETAILS**

**AVAILABLE SIZES**

12 in<sup>2</sup>/lf and 18 in<sup>2</sup>/lf NFA

**FACE HEIGHT AVAILABLE**

3.75"

**MATERIAL**

24 ga. Steel

**TEST COMPLIANCE**

California Wildfire Building Code Compliant

**FEATURES & BENEFITS**

- Twelve-ft. lengths for less material handling and quicker installation
- Hook-on flange designed to fit roof slopes 3:12 to 12:12
- Guarantees requisite intake airflow at the eave
- Warranties match applicable NDL terms and conditions
- All metal construction
- Pre-slotted fastening holes

## ENDURA™ VENT VENTED FASCIA



**PRODUCT USE**

Endura™ Vent Vented Fascia's hook-on flange is designed to fit a variety of roof pitches. Endura™ Vent Vented Fascia guarantees proper intake airflow at the eave to help prevent heat buildup and moisture accumulation under the roof covering. Metal construction eliminates wavy, untrue fascia boards and is available in 12'-0" lengths with pre-punched holes for quicker installation and lower labor costs.

**COMPOSITION & MATERIALS**

Endura™ Vent Vented Fascia's perforated closure is manufactured in 24 ga. steel and available in two popular colors: Bone White and Dark Bronze.

**APPLICATION**

Installation instructions are available at [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM), or by contacting our Technical Services Department.

**WARRANTY**

Endura™ Vent Vented Fascia is offered with warranties in varying length and wind speeds that match the terms and conditions offered in the applicable Malarkey Materials and Labor Warranty (NDL). For non-NDL applications this product is warranted against manufacturing defects for a period of ten (10) years and wind speeds up to 90 mph (145 kph). Contact your roofer, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Endura™ Vent Vented Fascia and other Malarkey products are available throughout North America and Pacific Rim countries. Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.

**ENDURA™ VENT VENTED FASCIA RECYCLED CONTENT**

	RECYCLED CONTENT	POST INDUSTRIAL	POST CONSUMER
<b>GALVANIZED STEEL</b>	25% - 50%	50% - 78%	22% - 50%

**TECHNICAL ASSISTANCE:**

Malarkey has technical services assistance available. Contact Malarkey for details: Call weekdays 7:00 am to 5:00 pm PST, at 800.545.1191 or 503.283.1191. [technicalinquiries@malarkeyroofing.com](mailto:technicalinquiries@malarkeyroofing.com)

**CORPORATE OFFICE:**

3131 N. Columbia Blvd. Telephone: 503.283.1191  
 Portland, OR 97217-7472 or 800.545.1191  
 P.O. Box 17217 Fax: 503.289.7644  
 Portland, OR 97217-0217

Effective 9/15  
 Supersedes all previously published data  
 Check for most current version on our website.