

TECHNICAL DETAILS

WEIGHT/ROLL 80 lbs. 36.3 kg	WEIGHT/SQUARE 40 lbs. 18.1 kg
WIDTH 39 ³ / ₈ " 1 m	LENGTH 66' 20.1 m
THICKNESS 55 mils nominal	COVERAGE 2 square
PERM RATING < 0.1 U.S. perms	ROLLS/PALLET 30

LAY LINES

2", 4", 12¹/₂", 18³/₄"
51 mm, 102 mm, 318 mm, 476 mm

TEST COMPLIANCE

ASTM D4601 Type II	ASTM D4869
ASTM D226 Type II	ASTM D6757 Type II
ICC APPROVAL ESR-1561	FBC APPROVALS #14807 #15214
ASTM E108 Class A Fire Rating	

FEATURES & BENEFITS

- Flexor™ SBS polymer modified asphalt
- Water-resistant underlayment
- Effective dry-in sheet
- UL Class A Fire Rated when installed with a Fire Rated Roof Covering

**FLEXOR™ SBS POLYMER
MODIFIED FIBERGLASS
UNDERLAYMENT**



PRODUCT USE

Right Start™ UDL is a Flexor™ SBS polymer modified asphalt membrane suitable for use as a water-resistant underlayment or dry-in sheet for steep slope roofing applications to include asphalt shingles, roof tile, and wood shakes and shingles. Right Start™ UDL is approved for use under fire-rated, code-compliant roof coverings. Please consult Malarkey's Technical Services Department for approval of roof systems.

COMPOSITION & MATERIALS

Right Start™ UDL is manufactured on a durable fiberglass mat, impregnated and coated on both sides with Flexor™ SBS polymer modified asphalt, and surfaced with a mineral release material.

APPLICATION

Right Start™ UDL shall be applied as specified. It is not intended as a permanently-exposed roofing surface but can be left uncovered for up to 90 days if necessary before the primary roof covering is installed. See Malarkey Specification Manual for specific installation instructions, and/or contact our Technical Services Department for details.

PRECAUTION

Right Start™ UDL should be stored on end prior to installation to prevent rolls from flattening. Malarkey recommends allowing Right Start™ UDL to warm up and relax prior to application in colder weather. Roof decks should be sound, dry, smooth, meet necessary local requirements, and provide positive drainage. Certain tiles with minimal contact to the surface of Right Start™ UDL may be prone to sliding.

WARRANTY

Right Start™ UDL is eligible for expanded warranty coverages relative to its use as a single roofing accessory or in combination with others in a complete Malarkey roofing system. Installed separately, it carries a 10-year product warranty against manufacturing defects. Contact your roofing contractor, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Right Start™ UDL and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products® inventory SKU designation for this product: UDL

PHYSICAL PROPERTIES	ASTM D4601 TYPE II	TYPICAL RESULTS
Maximum load, CM	44 lbf/in, minimum	Pass
Maximum load, MD	44 lbf/in, minimum	Pass
Pliability	No failures	Pass

TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available. Contact Malarkey for details: Call weekdays 7:00 am to 5:00 pm PST, at 800.545.1191 or 503.283.1191. technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217

Effective 2/17
Supersedes all previously published data
Check for most current version on our website.