

# SECURE START™ HT

LIMITED  
LIFETIME  
WARRANTY  
INCLUDED

## SecureStart™ HT

### SELF-ADHERING HIGH TEMPERATURE UNDERLAYMENTS

- Meets and exceeds ASTM D1970
- ASTM E108 Class A
- UV exposure up to six (6) months
- Limited Lifetime Warranty
- Class A fire-rated when installed with shingle roof coverings†
- 36" x 67' (0.91 m wide x 20.4 m long)

SecureStart™ HT is a product line of self-adhering, high temperature underlayments with superior thermal stability and adhesion properties in a temperature range from 40°F (4.4°C) to 240°F (116°C), making it the right choice for complete roof deck coverage under metal roofing applications. Its asphalt-based adhesive seals tight to the roof deck and around fasteners to protect against leaks caused by ice dams, extreme temperatures, and wind-driven rain. SecureStart™ HT underlayments are engineered with multiple layers for strength and durability, have a silicone-treated split-release film for ease of installation, and feature an anti-skid, walkable surface for roofer safety.

SecureStart™ HT underlayments can also be used under asphalt shingles, wood shakes & shingles, and mechanically-fastened roof tile. SecureStart™ HT joins other quality Malarkey products as part of the Secure Choice™ roof system.

SecureStart™ HT roofing underlayments are self-adhering and engineered for performance in high temperatures\*.

 **Malarkey**  
Roofing Products®

P.O. Box 17217, Portland, OR 97217  
503.283.1191 | 800.545.1191 | Fax: 503.289.7644  
[WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM)

\*For 405 SecureStart™ HT NS mastic must be used at seams. Please review installation instructions on our company website.

†Check with metal panel manufacturer for approval prior to installation.

Rev. 12/18