



TECHNICAL DETAILS

WIDTH ± 1/8" 10" 254 mm	LENGTH ± 1/8" 11 1/2" 292 mm
EXPOSURE 8 1/4" 210 mm	GRANULE ADHESION 0.35 g Typical Results
SHINGLES/BOX 30	BOXES/PALLET 42
LINEAR COVERAGE 20' 6.1 m	

NEX® POLYMER MODIFIED 10" WIDE, HIGH-PROFILE HIP AND RIDGE SHINGLES



TEST COMPLIANCE

ASTM D3161 Class F	ASTM E108 Class A Fire Rating
FBC APPROVAL #14809	ICC APPROVAL ESR-3150
UL RATING 2218 Class 4	
	

PRODUCT USE

224 EZ-Ridge™ XT Hip and Ridge Shingles (EZ-Ridge™ XT) are 10" wide, fortified with sustainable NEX® polymer modified asphalt technology, and designed to complement a number of asphalt shingle roofing systems. EZ-Ridge™ XT is an easy-to-install, high-profile roofing accessory providing resilient protection to hips and ridges, strong defense for ridge vents from weathering, and long-lasting appeal. EZ-Ridge™ XT features Scotchgard™ Protector from 3M to resist shingle discoloration due to algae growth. Malarkey roofing systems with algae resistant warranties *require* algae resistant hip and ridge shingles.

COMPOSITION & MATERIALS

EZ-Ridge™ XT Hip and Ridge Shingles are manufactured on a non-woven fiberglass mat and coated with Malarkey's unique NEX® polymer modified bitumen (asphalt). Its surface incorporates an innovative combination of ceramic granules that provide varied color, weatherability, algae protection, and now, smog reduction. EZ-Ridge™ XT Hip and Ridge Shingles are blended to match Malarkey field shingles.

APPLICATION

Installation instructions are available on the shingle box, at WWW.MALARKEYROOFING.COM, or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. EZ-Ridge™ XT should be attached to the roof shingles with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails long enough to penetrate all layers of shingles and completely through the roof deck or into the deck a minimum of 3/4" (19 mm). Staples are not allowed. Contact Malarkey's Technical Services Department when installing this product over ridge venting products.

FEATURES & BENEFITS

- Distinctive design with elevated profile
- Colors blended to match shingles
- Sustainable NEX® asphalt technology
- Exceptional all-weather performance
- UL 2218 Class 4 impact resistance
- 3M™ Smog-Reducing Granules
- 3M™ Scotchgard™ algae protection

PRECAUTION

For best results, Malarkey recommends EZ-Ridge™ XT be protected from the weather and stored on pallets in a cool, dry, well-ventilated area until applied. EZ-Ridge™ XT Hip and Ridge Shingles have a factory-applied, seal-down/adhesive strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. Should hand-sealing be necessary, apply shingle tab adhesive under each lower corner first and then fasten. Contact Malarkey for further conditions and instructions.

WARRANTY

EZ-Ridge™ XT Hip and Ridge Shingles are eligible for expanded warranty coverages relative to its use as a single roofing accessory or in combination with others in a complete Malarkey roofing system. When installed with algae resistant shingles, EZ-Ridge™ XT is covered by Malarkey's Limited Lifetime Scotchgard™ Protector warranty. Installed separately, it carries a 10-year product warranty against manufacturing defects. Contact your roofing contractor, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

EZ-Ridge™ XT and other Malarkey products are available throughout North America and Pacific Rim countries. Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products® inventory SKU number for this product: 224 10" EZ-Ridge™ XT Hip and Ridge Shingles featuring Scotchgard™ Protector from 3M

TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available. Contact Malarkey for details:
Call weekdays 7:00 am to 5:00 pm Pacific Time at 800.545.1191 or 503.283.1191.
technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217

Effective 9/20
Supersedes all previously published data
Check for most current version on our website.