


TECHNICAL DETAILS

WIDTH ± 1/8" 19 1/4" 489 mm	LENGTH ± 1/8" 38 1/4" 972 mm
EXPOSURE 5 3/4" 146 mm	GRANULE ADHESION 0.35 g Typical Results
SHINGLES/SQUARE 65 5 bundles/square	SQUARES/PALLET 6

NEX® POLYMER MODIFIED HEAVYWEIGHT DESIGNER SHINGLES



TEST COMPLIANCE

ASTM D7158 Class H	ASTM D3462
ASTM D3161 Class F	ASTM D3018 Type I
ASTM E108 Class A Fire Rating	UL RATING 2218 Class 4
CSA A123.5	

PRODUCT USE

The 290 Windsor® XL with Scotchgard™ is a unique, open-tab shingle fortified with sustainable NEX® polymer modified asphalt technology and manufactured for the premium designer market. It provides increased flexibility, higher tensile strength, tear and impact resistance, plus features Scotchgard™ Shingle Protector from 3M for added protection against discoloration and black streaks caused by algae. Windsor® XL has a 5 3/4" exposure, one of the largest in the industry. It shares the positive attributes of its 285 Windsor® shingle counterpart but has increased thickness, a nominal 1/4". Please consult Malarkey's Technical Services Department for approval of roof systems.

COMPOSITION & MATERIALS

Windsor® XL is a mineral-surfaced, self-sealing shingle, made with a NEX® polymer modified bitumen (asphalt) coating on fiberglass reinforcement, and carries a Class 'A' fire rating. Its surface incorporates an innovative combination of ceramic granules that provide varied color, weatherability, algae protection, and now, smog reduction.

FEATURES & BENEFITS

- Sustainable NEX® asphalt technology
- Exceptional all-weather performance
- Superior granular embedment
- 3M™ Scotchgard™ algae protection
- 3M™ Smog-Reducing Granules
- UL 2218 Class 4 impact resistance
- Limited Lifetime Shingle Warranty
- Limited & Enhanced Wind Warranties

APPLICATION

Shingles should be applied over a Malarkey underlayment or an approved, code-compliant substitute. Installation instructions are available on the shingle wrapper by scanning the corresponding Quick Response (QR) code, on our website at WWW.MALARKEYROOFING.COM, or by contacting your local Malarkey representative. Industry standards are found in NRCA manuals. Shingles should be attached to decking with approved fasteners, and Malarkey recommends the use of corrosion-resistant nails for this purpose. Staples are not allowed.

PRECAUTION

For best results, Malarkey recommends Windsor® XL shingles be protected from the weather and stored in a cool, dry, well-ventilated area until applied. Do not double-stack pallets. Do not use on roofs where the slope is less than 2:12 (2" [51 mm] per 12" [305 mm]). For slopes 2:12 up to 4:12 (4" [102 mm] per 12" [305 mm]), a double layer of underlayment is required (IBC & IRC have an exception for a single layer of ASTM D1970 underlayment in lieu of a double layer). Windsor® XL shingles have a factory-applied self-sealing strip that activates in warm weather. When applied in cold weather or windy locations, hand-sealing is recommended but not required if sealant activates. On slopes 21:12 (21" [533 mm] per 12" [305 mm]) and greater, hand-sealing of tabs and nine nails are required. Contact Malarkey for further conditions and instructions.

WARRANTY

The Windsor® XL shingle carries a Limited Lifetime Warranty, a 110 mph (177 kph) Limited Wind Warranty, and can be combined with other Malarkey products for a 140 mph (225 kph) Enhanced Wind Warranty. Windsor® XL also carries Malarkey's Limited Lifetime Scotchgard™ Protector Warranty against algae growth and staining. Contact your roofing contractor, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Windsor® XL and other Malarkey products are available throughout North America and Pacific Rim countries. Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products® inventory SKU number for this product: 290 Windsor® XL featuring Scotchgard™ Protector from 3M



TECHNICAL ASSISTANCE:

Malarkey has technical services assistance available. Contact Malarkey for details: Call weekdays 7:00 am to 5:00 pm Pacific Time at 800.545.1191 or 503.283.1191. technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Telephone: 503.283.1191
Portland, OR 97217-7472 or 800.545.1191
P.O. Box 17217 Fax: 503.289.7644
Portland, OR 97217-0217

Effective 8/19
Supersedes all previously published data
Check for most current version on our website.