

TECHNICAL PRODUCT DATA SHEET

LOW SLOPE - COMMERCIAL - LIQUID MEMBRANE SYSTEM - SKU: 756

TECHNICAL DETAILS

DIMENSIONS/ROLL 756-14 14" x 164' 356 mm x 50 m

THICKNESS 30-40 mils

WEIGHT

FORM/COLOR Solid

White

110 g/m²

WATER ABSORPTION <1%

FEATURES & BENEFITS

- Used w/non-fibered PMMA resin as reinforcement
- EZ Seal membranes are monolithic, flexible and seamless
- Ideal for access-restricted areas and difficult waterproofing conditions

EZ SEAL FLEECE

PRODUCT USE

EZ Seal Fleece is used to improve tear strength, puncture resistance and crack-bridging capabilities of EZ Seal Non-Fibered PMMA Resin while maintaining membrane uniformity. Malarkey Roofing Products® EZ Seal System is waterproof, flexible, self-adhering, and ideal for access-restricted and difficult waterproofing conditions. EZ Seal conforms and bonds directly to the substrate and penetrations, eliminates the need for caulk and pitch pans, and is virtually maintenance-free.

COMPOSITION & MATERIALS

EZ Seal Fleece is a non-woven, chopped strand, fabric reinforcement and used with EZ Seal Non-Fibered PMMA Resin. Standard (760). EZ Seal Fleece is available in 14-inch widths.

APPLICATION/INSTALLATION

EZ Seal Fleece is used with EZ Seal Non-Fibered PMMA Resin. Apply to substrates prepared as specified in the EZ Seal Application Instructions. Allow a 2" (51 mm) overlap at side laps, 4" (102 mm) at end laps, 4" (102 mm) at all flashings, and 5% for waste. Contact Malarkey's Technical Services Department for details.

PRECAUTIONS

Always store rolls of EZ Seal Fleece upright in a cool and dry location. Do not store flat as this deforms the rolls and creases the fabric. Shelf life is indefinite with proper storage. Refer to product SDS prior to use or handling, but EZ Seal Fleece requires no special measures and may disposed of in standard landfills. Products used with EZ Seal Fleece may be flammable or explosive.

EMERGENCY INFORMATION:

For Chemical Emergency, Spill Leak, Fire Exposure or Accident Call CHEMTREC Day or Night; in North America 800-424-9300

WARRANTY

Malarkev Roofing Products[®] offers various warranties to meet specific requirements. Contact your roofer, local distribution center or Malarkev for full details. See below for TECHNICAL ASSISTANCE contact information.

EZ Seal and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit WWW.MALARKEYROOFING.COM for additional product information and availability.

Note: Malarkey Roofing Products® (Malarkey) inventory SKU number for this product: 756-14 EZ Seal Fleece

TECHNICAL ASSISTANCE:

Malarkev has technical services assistance available. Contact Malarkey for details: Call weekdays 7:00 am to 5:00 pm Pacific Time at 800.545.1191 or 503.283.1191. technicalinquiries@malarkeyroofing.com

CORPORATE OFFICE:

3131 N. Columbia Blvd. Portland, OR 97217-7472 P.O. Box 17217 Portland, OR 97217-0217

Telephone: 503.283.1191 or 800.545.1191 Fax: 503.289.7644

Page 1 of 1

Supersedes all previously published data Check for most current version on our website.

Effective 11/20

WWW.MALARKEYROOFING.COM

LOW SLOPE - COMMERCIAL - LIQUID MEMBRANE SYSTEM - EZ SEAL[™] - FLEECE - SKU: 756