

**TECHNICAL DETAILS****DIMENSIONS/ROLL 756-14**14" x 164'  
356 mm x 50 m**DIMENSIONS/ROLL 756-41**41" x 164'  
1.04 m x 50 m**THICKNESS**

30-40 mils

**WEIGHT**110 g/m<sup>2</sup>**FORM/COLOR**Solid  
White**WATER ABSORPTION**

&lt;1%

**FEATURES & BENEFITS**

- Used w/non-fibered PMMA resin as reinforcement
- EZ Seal membranes are monolithic, flexible and seamless
- Ideal for access-restricted areas and difficult waterproofing conditions

**EZ SEAL FLEECE****PRODUCT USE**

EZ Seal Fleece is used to improve tear strength, puncture resistance and crack-bridging capabilities of EZ Seal Non-Fibered PMMA Resin while maintaining membrane uniformity. Malarkey Roofing Products® EZ Seal System is waterproof, flexible, self-adhering, and ideal for access-restricted and difficult waterproofing conditions. EZ Seal conforms and bonds directly to the substrate and penetrations, eliminates the need for caulk and pitch pans, and is virtually maintenance-free.

**COMPOSITION & MATERIALS**

EZ Seal Fleece is a non-woven, chopped strand, fabric reinforcement and used with EZ Seal Non-Fibered PMMA Resin, Standard (760). EZ Seal Fleece is available in 14-inch and 41-inch widths.

**APPLICATION/INSTALLATION**

EZ Seal Fleece is used with EZ Seal Non-Fibered PMMA Resin. Apply to substrates prepared as specified in the EZ Seal Application Instructions. Allow a 2" (51 mm) overlap at side laps, 4" (102 mm) at end laps, 4" (102 mm) at all flashings, and 5% for waste. Contact Malarkey's Technical Services Department for details.

**PRECAUTIONS**

Always store rolls of EZ Seal Fleece upright in a cool and dry location. Do not store flat as this deforms the rolls and creases the fabric. Shelf life is indefinite with proper storage. Refer to product SDS prior to use or handling, but EZ Seal Fleece requires no special measures and may be disposed of in standard landfills. Products used with EZ Seal Fleece may be flammable or explosive.

**EMERGENCY INFORMATION:**

For Chemical Emergency, Spill Leak, Fire Exposure or Accident  
Call CHEMTREC Day or Night; in North America 800-424-9300

**WARRANTY**

Malarkey Roofing Products® offers various warranties to meet specific requirements. Contact your roofer, local distribution center or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

EZ Seal and other Malarkey products are available throughout North America and Pacific Rim countries.

Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.

Note: Malarkey Roofing Products® (Malarkey) inventory SKU number for this product: 756-14, 756-41 EZ Seal Fleece

**TECHNICAL ASSISTANCE:**

Malarkey has technical services assistance available.  
Contact Malarkey for details:  
Call weekdays 7:00 am to 5:00 pm PST,  
at 800.545.1191 or 503.283.1191.  
[technicalinquiries@malarkeyroofing.com](mailto:technicalinquiries@malarkeyroofing.com)

**CORPORATE OFFICE:**

3131 N. Columbia Blvd. Telephone: 503.283.1191  
Portland, OR 97217-7472 or 800.545.1191  
P.O. Box 17217 Fax: 503.289.7644  
Portland, OR 97217-0217