

Flexor™ SBS Polymer Modified Fiberglass Underlayment

Right Start™ UDL

- Approx. Wt./Roll: 80 lbs. (36.3 kg)
- Coverage: 2 squares
- Width: 39³/₈" (1 m)
- Length: 66' (20.1 m)
- Thickness: 55 mils (nominal)
- Rolls/Pallet: 30

- ASTM D4601 Type II
- ASTM D4869
- ASTM D226 Type II
- ASTM D6757 Type II
- ICC Approval - ESR-1561
- FBC Approvals - #14807 & #15214
- ASTM E108 Class A Fire Rating



Works great under tile!




**Fiberglass Barrier Provides
Dependable Water-Resistant
Protection**

**Effective Dry-in Sheet for Steep
Slope Applications**

**UL Class A Fire Rated When Installed
with a Fire Rated Roof Covering**

**Increased Walkability Versus
Traditional Roofing Felts**

**Performing in All Weather
Conditions for Over 25 Years**




QUALITY DESIGN

Manufactured on a durable fiberglass mat, impregnated and coated on both sides with SBS asphalt, and surfaced with a mineral release material.



FLEXOR™ POLYMER MODIFIED ASPHALT

Asphalt technology increases flexibility, cold weather application, and tear strength.



WARRANTIES

- 10-year product warranty
- Optional *Accessory Warranty* when part of a greater roof system
- Eligible for *Concrete and Clay Tile Underlayment Warranty* for up to 20 years