

**TECHNICAL DETAILS**

<b>WEIGHT/ROLL</b> 80 lbs. 36.3 kg	<b>WEIGHT/SQUARE</b> 40 lbs. 18.1 kg
<b>WIDTH</b> 39 <sup>3</sup> / <sub>8</sub> " 1 m	<b>LENGTH</b> 66' 20.1 m
<b>THICKNESS</b> 55 mils nominal	<b>COVERAGE</b> 2 square
<b>PERM RATING</b> <0.1 U.S. perms	<b>ROLLS/PALLET</b> 30

**LAY LINES**  
2", 4", 12<sup>1</sup>/<sub>2</sub>", 18<sup>3</sup>/<sub>4</sub>"  
51 mm, 102 mm, 318 mm, 476 mm

**TEST COMPLIANCE**

<b>ASTM</b> D4601 Type II	<b>ASTM</b> D4869
<b>ASTM</b> D226 Type II	<b>ASTM</b> D6757 Type II
<b>ICC APPROVAL</b> ESR-1561	<b>FBC APPROVALS</b> #14807 #15214
<b>ASTM</b> E108 Class A Fire Rating	

**FEATURES & BENEFITS**

- Fortified with sustainable NEX<sup>®</sup> polymer modified asphalt technology
- Tear and water-resistant underlayment
- Effective dry-in sheet
- UL Class A Fire Rated when installed with a Fire Rated Roof Covering

**NEX<sup>®</sup> POLYMER MODIFIED FIBERGLASS UNDERLAYMENT**



**PRODUCT USE**

Right Start<sup>™</sup> UDL is a roofing membrane designed for use as a water-resistant underlayment and dry-in sheet for steep slope roofing applications to include asphalt shingles, roof tile, and wood shakes and shingles. It is fortified with sustainable NEX<sup>®</sup> polymer modified asphalt, technology that utilizes polymers from repurposed materials to refine the physical characteristics necessary for peak product performance and longer service life. Right Start<sup>™</sup> UDL is approved for use under fire-rated, code-compliant roof coverings; please consult Malarkey's Technical Services Department for sanction of roof systems.

**COMPOSITION & MATERIALS**

Right Start<sup>™</sup> UDL is manufactured on a non-woven fiberglass mat, impregnated and coated on both sides with NEX<sup>®</sup> polymer modified asphalt, and surfaced with a mineral release material.

**APPLICATION**

Right Start<sup>™</sup> UDL shall be applied as specified. It is not intended as a permanently-exposed roofing surface but can be left uncovered for up to 90 days if necessary before the primary roof covering is installed. Installation instructions can be found on our website at [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) or by contacting our Technical Services Department.

**PRECAUTION**

Right Start<sup>™</sup> UDL should be stored on end to prevent rolls from flattening. Malarkey recommends allowing Right Start<sup>™</sup> UDL to warm up and relax prior to application in colder weather. Roof decks should be sound, smooth, meet necessary local requirements, and be dry at the time of installation. Minimum approved slope is 2" (51 mm) per 12" (305 mm). Certain tiles with minimal contact to the surface of Right Start<sup>™</sup> UDL may be prone to sliding.

**WARRANTY**

Right Start<sup>™</sup> UDL is eligible for expanded warranty coverages relative to its use as a single roofing accessory or in combination with others in a complete Malarkey roofing system. Installed separately, it carries a 10-year product warranty against manufacturing defects. Contact your roofing contractor, local distribution center, or Malarkey for full details. See below for TECHNICAL ASSISTANCE contact information.

Right Start<sup>™</sup> UDL and other Malarkey products are available throughout North America and Pacific Rim countries. Visit [WWW.MALARKEYROOFING.COM](http://WWW.MALARKEYROOFING.COM) for additional product information and availability.

Note: Malarkey Roofing Products<sup>®</sup> inventory SKU designation for this product: UDL

PHYSICAL PROPERTIES	ASTM D4601 TYPE II	TYPICAL RESULTS
Maximum load, CM	44 lbf/in, minimum	Pass
Maximum load, MD	44 lbf/in, minimum	Pass
Pliability	No failures	Pass